

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Cancel)
2. (Currently Amended) The A latch of claim 1, including for use in a vehicle having a rear seat with a fold-down seatback, the latch comprising:
a latch assembly configured to releaseably engage a striker member coupled to the vehicle, the latch assembly comprising:
a catch plate configured with two prongs and pivotally mounted on a support plate;
a hook plate with two camming surfaces configured to engage at least one of the prongs with the hook plate pivotally mounted on the support plate; and
an intermediate plate pivotally mounted on the support plate and configured to selectively engage the catch plate and the hook plate, wherein movement of the engaged prong is restricted in any direction when the hook plate is in a locked position.
3. (Currently Amended) The latch of claim 1 2, wherein the latch assembly is coupled to the seatback.
4. (Original) The latch of claim 2, including an overmold mounted on each prong and aligned to contact the striker member during operation of the seatback latch to provide a positive engagement between the catch plate and the striker to minimize free play and buzzes, squeaks and rattles.
5. (Original) The latch of claim 4, wherein the overmold is composed of plastic.
6. (Currently Amended) The latch of claim 1 2, including a first biasing member coupled to the catch plate and support ~~member~~ plate.
7. (Currently Amended) The latch of claim 1 6, including a second biasing member coupled to the hook plate and support ~~member~~ plate.
8. (Cancel)

9. (Currently Amended) The A seat of claim 8 for a vehicle, the seat comprising:
a seat base coupled to the vehicle;
a seatback coupled to the seat base and configured to rotate from a seating position to a stored position; and
a latch coupled to the seatback, the latch comprising:
a striker member coupled to the vehicle; and
a latch assembly configured to releaseably engage the striker member, the latch assembly comprising:
a catch plate configured with two prongs and pivotally mounted on a support plate;
a hook plate with two camming surfaces configured to engage at least one of the prongs with the hook plate pivotally mounted on the support plate; and
an intermediate plate pivotally mounted on the support plate and configured to selectively engage the catch plate and hook plate, wherein movement of the engaged prong is restricted in any direction when the hook plate is in a locked position.
10. (Currently Amended) The seat of claim 8 9, wherein the latch assembly is coupled to the seatback.
11. (Original) The seat of claim 9, including an overmold mounted on each prong and configured to contact the striker member during operation of the latch to prevent buzzes, squeaks and rattles.
12. (Original) The seat latch of claim 11, wherein the overmold is composed of plastic.
13. (Currently Amended) The seat latch of claim 8 9, including a first biasing member coupled to the catch plate and support ~~member~~ plate.
14. (Currently Amended) The seat latch of claim 8 13, including a second biasing member coupled to the hook plate and support ~~member~~ plate.